FOR S

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-14-110 Relating to Certification of New Motor Vehicles

TOYOTA MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Orders G-45-3 and G-45-4;

IT IS ORDERED AND RESOLVED: That 1988 model-year Toyota Motors Corporation exhaust emission control systems are certified as described below for gasoline-powered passenger cars:

| Engine Family | | placement (Cubic Inches) | Exhaust Emission Control Systems (Special Features) | |
|---------------|------------------------|-----------------------------|------------------------------------------------------------------------------------------------------|--|
| JTY2.0V5FBB8 | Y2.0V5FBB8 2.0 (121.9) | | Exhaust Gas Recirculation Three-Way Catalyst Oxygen Sensor (Electronic Port Fuel Injection) | |

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The following are the emission standards for this engine family:

| Hydrocarbons | Carbon Monoxide | Nitrogen Oxides | |
|----------------|-----------------|-----------------------|--|
| Grams per Mile | Grams per mile | <u>Grams per Mile</u> | |
| 0.39 | 7.0 | 0.7 | |

The following are the certification emission values for this engine family:

| Hydrocarbons | Carbon Monoxide | Nitrogen Oxides | | |
|----------------|-----------------|-----------------|--|--|
| Grams per Mile | Grams per Mile | Grams per Mile | | |
| 0.16 | 1.4 | 0.1 | | |

BE IT FURTHER RESOLVED: That the listed models were certified to the optional NOx emission standard thereby making the vehicle manufacturer subject to Section 1960.1.5 of Title 13, California Administrative Code which includes recall liability for emission control components up to 7 years or 75,000 miles if found defective by the Executive Officer.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Gasoline-Powered Motor Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" (Title 13, California Administrative Code, Section 2290) for the aforementioned model-year.

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high altitude requirements and highway emission standards as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Tune-Up Label Specifications" (Title 13, California Administrative Code, Section 1965) for the aforementioned model year.

BE IT FURTHER RESOLVED: That the vehicle models listed have been granted an exemption from compliance with the requirements of the "Malfunction and Diagnostic System for 1988 and Subsequent Model Year[s] ..." (Title 13, California Administrative Code, Section 1968) for the aforementioned model year.

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty regulations (Title 13, California Administrative Code, Section 2035 et seq.) and with Health and Safety Code Section 43204.

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this

17¹ day of August, 1987.

K. D. Drachand, Chief Mobile Source Division

Maun

| 1988 AIR RE | SOURCES BOARD SUPPLEMENTAL DA | ATA SHEET E.O. # $A - 14 - 110$ |
|--------------------------------|-------------------------------------------------------|---------------------------------|
| | | Pagel |
| Manufacturer Toyota Motor Corp | oration Engine Family | JTY2.0V5FBB8 |
| Evaporative Family EV-E | Engine Type | quantum dine |
| | Liters (CID) | |
| ABBREVIATIONS | | |
| | | |
| | | |
| Ignition System | Exhaust Emissions Control Sy | stem Special Features |
| CA-Centrifugal Advance | AIP-Air Injection-Pump | CCV-Combustion |
| ECU-Electronic Control Unit | AIV-Air Injection-Valve | Chamber Valve |
| EI-Electronic Ignition | DBC-Dual Bed Catalyst | CFI-Central Fuel |
| ESAC-Electronic Spark Advance | EGR-Exhaust Gas Recirculation | |
| Control | EIC-Electronic Injection Con | ntrol DID-Diesel |
| VA-Vacuum Advance | EM-Engine Modification | Injection- |
| VR-Vacuum Retard | OC-Oxidation Catalyst | Direct |
| | OS-Oxygen sensor | DIP-Diesel |
| | HOS-Heated Oxygen Sensor SPL-Smoke Puff Limiter or | Injection- |
| | Throttle Delay | Prechamber |
| | TOC-Trap Oxidizer, Continual | EFI-Electronic |
| Fuel System | TOP-Trap Oxidizer, Periodica | · = |
| CFI, CL, DID, DIP, EFI, MFI | TWC-Three-Way Catalyst | or aftercooler |
| nV-nVenturi Carburetor | WUOC-Warm-Up Oxidation Catal | |
| | WUTWC-Warm-Up Three-Way Cata | |
| | - <u>-</u> | OBD-On-Board |
| | | Diagnostics |
| | | TC-Turbocharger |
| VEHICLE MODELS : | | |
| Camry Camry & | vagon Celica C | elica convertible |
| SV21L-UEMDKA SV21LG-U | | T162L-BKMVKA |
| -UEMNKA -U | WPDKA -BCMVKA | -BKPVKA |
| | WPNKA -BCPSKA | |
| -UEPDKA | -BCPVKA | |
| -UEPNKA | -BLMVKA | |
| -UEPBKA | -BLPVKA | |
| Engine: Front x Mid. | Rear | |
| Drive: FWD _x RWD | 4WD Full time 4W | VD Part time |
| | | |

Page : 17.11-21 _ssued : 05/26/87

B.O. * A-14-110

| 1988 AIR RESOURCES | BOARD | SUPPLEMENTAL | DATA | SHEET |
|--------------------|-------|--------------|------|-------|
|--------------------|-------|--------------|------|-------|

| Passenger | Cars <u>x</u> Light-1 | outy Tru | ıcks | _ Medium-Duty | Vehicles _ | _ Gas <u>x</u> D | lesel |
|------------|--------------------------------------------------------------------------------------|----------|-------------------------|-------------------------|---------------------------------------------------------------------|------------------|---------------------------------------------------------|
| Manufactu | rer <u>Toyota M</u> | tor Cor | poratio | n Engir | ne family | JTY2.0\ | /5PBB8 |
| | D)2.0 | | | | | | |
| | Control Sys. (Spe | | | | • | | |
| Engine | Vehicle Models (If Coded see attachment) (Dyno Hp: Refer to 08.13.03.00) | Туре | Test | EEC.EI.ESAC Part No. | Fuel System CL. EFI Part No. [Computer] [Air flow meter] [Injector] | EGR Valve | Catalyst Part No. |
| 1, 2 | SV21L-UEMDKA -UEMNKA -UEMBKA - SV21LG-UWMDKA | M5 | 3,125 3,250 3,250 | 89661-20440 | 89661-20440 22250-74100 23250-74060 | 25620-74110 | (Manifold converter)*l |
| lR1, · 2R1 | SV21LG OWPDRA | | | 89661-20441 | 89661-20441 22250-74100 23250-74060 | | 25508-74022 (Manifold converter)*2 25508-74080 |
| 3, 4 | SV21L-UEPBKA | A4 | 3,250 | 89661-20440 | 89661-20440 22250-74100 23250-74060 | 25620-74120 | (Manifold converter)*3 |
| 3R1, 4R1 | | | · · | | 89661-20441 22250-74100 23250-74060 | | |
| 5.6 | -UEPNKA SV21LG-UWPDKA | | 3,125 3,250 | | 89661-32230 22250-74100 23250-74060 | | |
| 5R1, 6R1 | -UWPNKA | , | | | 89661-32231 22250-74100 23250-74060 | | |

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

[Note] *1 : Before Running change 88-TR-7.

*2 : After Running change 88-TR-7.

*3 : After Running change 88-TR-14.

Page : 17.11-22

Issued: 05/26/87 Rev. 1: 06/26/87 88-TR-4: 09/30/87 88-TR-7: 11/30/87

88-TR-14 : 03/10/88

| Engine | Vehicle Models (If Coded see | Trans. | Test | BEC, EI, ESAC | Fuel System | EGR Valve | Catalyst |
|-----------|------------------------------------------------|--------|-------------------------|------------------------|-------------------------------------------------|-------------|----------------------------------------------------------------------------------------------------------------------------------|
| code | attachment) (Dyno Hp: Refer to 08.13.03.00) | Type | We1ght | Part No. [Computer] | Part No. [Computer] [Air flow meter] [Injector] | Part No. | Part No. |
| 7, 8 | ST162L-BCMSKA -BCMVKA -BKMVKA -BLMVKA | M5 | 2,875 3,000 3,125 | 89661-20440 | 89661-20440 22250-74120 23250-74060 | 25620-74110 | 25508-74021 (Manifold converter)*1 25508-74022 (Manifold converter)*2 25508-74080 (Manifold converter)*3 |
| 7R1, 8R1 | | | | 89661-20441 | 89661-20441 22250-74120 23250-74060 | | |
| 9, 10 | ST162L-BCPSKA -BCPVKA -BKPVKA -BLPVKA | A4 | 3,000 3,125 3,250 | 89661-20440 | 89661-20440 22250-74120 23250-74060 | | |
| 9R1, 10R1 | DEFACE | | | 4 | 89661-20441 22250-74120 23250-74060 | | |

Comments: See page one for abbreviations and evaporative emission family identification. Please refer to manufacturer's HP list for correct dyno test HP settings based on model and equipment. If two test weights are listed, the lower weight will be used for testing.

[Note] *1 : Before Runnina change 88-TR-7.

*2 : After Running change 88-TR-7.

*3 : After Running change 88-TR-14.

Page : 17.11-22.1

88-TR-4: 09/30/87 88-TR-7: 11/30/87 88-TR-14: 03/10/88